

SHELF LIFE GUIDE

ITEM	UPC CODE	PRODUCT CATEGORY	SHELF LIFE	STORAGE
Superior Anti-Spatters				
AS-SB-A	81004830-001	Solvent-Based Anti-Spatter	2 YEARS	Store in compliance with NFPA 30B code for the Manufacture and Storage of Aerosol Products in accordance with the appropriate aerosol level. All WCI aerosol boxes are marked with required Level on the front facing product label, store according to Level as marked.
AS-WB-A	81004830-002	Water-Based Anti-Spatter	2 YEARS	
AS-CER-A	81004830-003	Ceramic-Based Anti-Spatter	2 YEARS	
Superior Nozzle Tip Dip				
SNTD-16	81004830-007	Superior Nozzle Tip Dip	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
SNTD-1GR	81004830-008		5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
Superior Welding Wire Pads				
SWW-LP-6	81004830-009	Superior Welding Wire Lubricated Pads	3 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
SWW-NT-6	81004830-010	Superior Welding Wire Untreated Pads	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
Coolant System Fluids				
SCF-1GR	81004830-011	Safe Cooling Fluid - Standard Temperature (+5°F/-15°C)	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
SCF-5GP	81004830-012		5 YEARS	
SCF-55GPD	81004830-013		5 YEARS	
RTCF-1GR	81004830-014	Cooling Fluids - Regular Temperature (+15°F/-9°C)	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
RTCF-5GP	81004830-015		5 YEARS	
RTCF-55GPD	81004830-016		5 YEARS	
MTCF-1GR	81004830-017	Cooling Fluids - Medium Temperature (0°F/-18°C)	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
MTCF-5GP	81004830-018		5 YEARS	
MTCF-55GPD	81004830-019		5 YEARS	
LTCF-1GR	81004830-020	Cooling Fluids - Low Temperature (-35°F/-37°C)	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
LTCF-5GP	81004830-021		5 YEARS	
LTCF-55GPD	81004830-022		5 YEARS	
Dye Penetrant Inspection				
RDP-SOL-A	81004830-023	Solvent Removable - Method C - Red Dye Penetrant	2 YEARS	Store in compliance with NFPA 30B code for the Manufacture and Storage of Aerosol Products in accordance with the appropriate aerosol level. All WCI aerosol boxes are marked with required Level on the front facing product label, store according to Level marked.
RDP-WAT-A	81004830-024	Water Washable - Method A - Red Dye Penetrant	2 YEARS	
WDP-A	81004830-025	White Developer Powder - Form e - Nonaqueous Type 2	2 YEARS	
CAR-A	81004830-026	Cleaner and Remover - Class 2 - Nonhalogenated	2 YEARS	
NUCCAR-A	81004830-027	Cleaner and Remover - Class 2 - Nonhalogenated	2 YEARS	
LPI-K-8	81004830-028	Liquid Penetrant Inspection Kit	2 YEARS	
Oxygen Approved Leak Detectors				
LDREG-8OZ	81004830-029	Type I Oxygen Approved Leak Detector Reg Temp	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
LDREG-1GR	81004830-030		5 YEARS	
LDREG-5GP	81004830-031		5 YEARS	
LDREG-55GPD	81004830-032		5 YEARS	
LDLOW-8OZ	81004830-033	Type II Oxygen Approved Leak Detector Low Temp	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
LDLOW-1GR	81004830-034		5 YEARS	
LDLOW-5GP	81004830-035		5 YEARS	
LDLOW-55GPD	81004830-036		5 YEARS	
LDMID-1GR	81004830-037	Oxygen Approved Leak Detector Mid Temp	5 YEARS	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible materials. Protect container(s) against physical damage.
LDMID-5GP	81004830-038		5 YEARS	
LDMID-55GPD	81004830-039		5 YEARS	

The information provided in this document is believed to be accurate as of the date this document was prepared (see REVISION and DATE below). No warranty of merchantability, fitness for any particular use, or any other warranty, expressed or implied, is made regarding the accuracy or completeness of the information contained herein, or the results to be obtained from the use of this information, and we assume no liability resulting from the use of such information. In addition, users shall make their own determination as to the suitability of the product or products described herein for their intended use, and in no event shall Welding Chemicals Inc. (WCI) be liable for any claims, losses, or damages for any lost profits or any special, indirect, incidental, consequential or exemplary damages resulting from such product use. Additional product information is available in product specific technical data sheets (TDS's), and safety data sheets (SDS's), which can be downloaded from www.weldingchemicalsinc.com.